



## CARBON STEEL HOOKS

Strong, durable hooks predominantly used in winching and hoisting.

- Forged from high-strength steel and heat treated
- Batch destruction testing
- Factor of Safety 5:1
- Fatigue tested at 1,5 times working load limit
- 100% magnetic particle tested


### EYE HOOK - HKEH



#### TECHNICAL SPECIFICATIONS

| Product Code | Working Load Limit (t) | Breaking Load Limit (b) | D  | E    | H    | K     | M    | L     |
|--------------|------------------------|-------------------------|----|------|------|-------|------|-------|
| HKEH00750    | 0.75                   | 3.75                    | 19 | 22   | 19   | 82    | 16   | 110   |
| HKEH01000    | 1                      | 5                       | 23 | 23   | 21   | 93.5  | 17.5 | 125   |
| HKEH01500    | 1.5                    | 7.5                     | 28 | 24   | 26   | 103   | 21   | 140.5 |
| HKEH02000    | 2                      | 10                      | 31 | 27.5 | 28   | 119   | 23   | 162   |
| HKEH03000    | 3                      | 15                      | 39 | 33   | 37   | 146   | 30   | 201   |
| HKEH05000    | 5                      | 25                      | 51 | 40   | 46.5 | 186.5 | 38   | 256   |
| HKEH07500    | 7.5                    | 37.5                    | 62 | 51   | 57   | 231.5 | 46   | 317   |
| HKEH10000    | 11*                    | 55                      | 62 | 51   | 57   | 231.5 | 46   | 317   |
| HKEH15000    | 15*                    | 75                      | 73 | 57   | 70   | 260   | 55   | 360   |

\*Alloy Steel - Factor of Safety 4:1




### SWIVEL HOOK - HKSW



#### TECHNICAL SPECIFICATIONS

| Product Code | Working Load Limit (t) | A    | E    | B    | H    | K     | L     | M    |
|--------------|------------------------|------|------|------|------|-------|-------|------|
| HKSW00750    | 0.75                   | 32.0 | 17.0 | 22.5 | 9.0  | 108.3 | 137.0 | 16.0 |
| HKSW01000    | 1                      | 37.5 | 22.5 | 29.5 | 12.0 | 133.5 | 163.5 | 16.0 |
| HKSW01500    | 1.5                    | 42.5 | 26.0 | 33.0 | 15.8 | 150.5 | 192.0 | 17.5 |
| HKSW02000    | 2                      | 42.5 | .0   | 33.0 | 15.8 | 163.0 | 209.0 | 23.0 |
| HKSW03000    | 3                      | 48.0 | 32.5 | 39.0 | 18.0 | 191.0 | 246.0 | 31.0 |
| HKSW05000    | 5                      | 64.0 | .0   | 53.0 | 25.0 | 243.5 | 313.0 | 34.0 |
| HKSW07500    | 7.5                    | 70.0 | 49.5 | 53.0 | 28.5 | 277.0 | 364.0 | 41.5 |
| HKSW10000    | 11*                    | 70.0 | 49.5 | 53.0 | 28.5 | 277.0 | 364.0 | 41.5 |
| HKSW15000    | 15*                    | 79.0 | 54.5 | 62.0 | 32.0 | 332.0 | 431.0 | 55.7 |

\*Alloy Steel - Factor of Safety 4:1




### SHANK HOOK - HKSH



#### TECHNICAL SPECIFICATIONS

| Product Code | Working Load Limit (t) | B     | E    | C    | M    | G    | F     | D    | L     |
|--------------|------------------------|-------|------|------|------|------|-------|------|-------|
| HKSH0750     | 0.75                   | 73.0  | 25.0 | 15.0 | 18.0 | 16.0 | 51.0  | 32.0 | 127.0 |
| HKSH1000     | 1                      | 80.3  | 25.5 | 16.7 | 20.0 | 18.0 | 58.0  | 35.0 | 147.0 |
| HKSH1500     | 1.5                    | 92.0  | 30.4 | 18.4 | 23.0 | 22.5 | 67.0  | 38.0 | 165.0 |
| HKSH2000     | 2                      | 105.0 | 32.0 | 22.4 | 26.0 | 24.0 | 69.0  | 41.4 | 177.5 |
| HKSH3000     | 3                      | 126.0 | 38.5 | 29.5 | 32.0 | 29.0 | 82.0  | 51.0 | 216.5 |
| HKSH5000     | 5                      | 167.0 | 47.0 | 35.8 | 40.0 | 36.0 | 95.5  | 64.0 | 262.5 |
| HKSH7500     | 7.5                    | 192.0 | 61.0 | 46.0 | 51.0 | 47.7 | 111.2 | 76.0 | 323.0 |
| HKSH10000    | 10                     | 214.6 | 66.0 | 50.8 | 55.6 | 55.5 | 114.0 | 82.5 | 342.0 |



### SLIDING CHOKER HOOK- HKSH



#### TECHNICAL SPECIFICATIONS

| Product Code | Working Load Limit (t) | D    | E    | H     | K    | L     |
|--------------|------------------------|------|------|-------|------|-------|
| HKSC10/13    | 1.6                    | 17.0 | 50.0 | 71.0  | 21.0 | 132.0 |
| HKSC16       | 2.0                    | 22.0 | 63.5 | 79.0  | 23.0 | 151.5 |
| HKSC19       | 3.0                    | 28.0 | 69.0 | 103.0 | 29.0 | 170.0 |
| HKSC26       | 5.0                    | 32.5 | 85.7 | 135.0 | 38.0 | 213.0 |

